

## CSE-Series comparison chart

	<b>CSE1600</b>	<b>CSE2500</b>	<b>CSE3150</b>	<b>CSE3500</b>
<b>Material</b>	<i>Powder painted aluminium and POM</i>	<i>Powder painted aluminium and POM</i>	<i>Powder painted aluminium and POM</i>	<i>Powder painted aluminium and POM</i>
<b>Weight</b>	<i>14 Kg</i>	<i>23 Kg</i>	<i>26 Kg</i>	<i>32 Kg</i>
<b>Dimensions</b>	<i>407 x 395 x 236mm</i>	<i>610 x 410 x 265mm</i>	<i>649 x 452 x 316mm</i>	<i>765 x 512 x 316mm</i>
<b>Capacity</b>	<i>20 000 fish/unit/hour (100g)</i>	<i>20 tonnes/unit/hour (1Kg)</i>	<i>25 tonnes/unit/hour (1Kg)</i>	<i>30 tonnes/unit/hour (1Kg)</i>
<b>Power Consumption</b>	<i>10W</i>	<i>15W</i>	<i>15W</i>	<i>17W</i>
<b>Power supply</b>	<i>Powered by the Control Unit</i>	<i>Powered by the Control Unit</i>	<i>Powered by the Control Unit</i>	<i>Powered by the Control Unit</i>
<b>Flange connection</b>	<i>DN150</i>	<i>DN250</i>	<i>DN300</i>	<i>DN350</i>
<b>Fish size</b>	<i>1g to 1Kg</i>	<i>3g to 7Kg</i>	<i>3g to 12Kg</i>	<i>10g to 18Kg</i>
<b>Accuracy</b>	<i>98-100%</i>	<i>98-100%</i>	<i>98-100%</i>	<i>98-100%</i>
<b>Arrangement</b>	<i>Approx. 30 ° tilt forward. 0 to ¼ pipe transport water</i>	<i>Approx. 30 ° tilt forward. 0 to ¼ pipe transport water</i>	<i>Approx. 30 ° tilt forward. 0 to ¼ pipe transport water</i>	<i>Approx. 30 ° tilt forward. 0 to ¼ pipe transport water</i>
<b>Flow speed</b>	<i>2,5 - 3 m/s</i>	<i>2,5 - 3 m/s</i>	<i>2,5 - 3 m/s</i>	<i>2,5 - 3 m/s</i>
<b>Standard cable length included</b>	<i>10 meters</i>	<i>10 meters</i>	<i>10 meters</i>	<i>10 meters</i>
<b>Requirements</b>	<i>AquaScan Control Unit</i>	<i>AquaScan Control Unit</i>	<i>AquaScan Control Unit</i>	<i>AquaScan Control Unit</i>